## **Crosswise Convection Electric Convection Oven - 3** Grids

ITEM #	
MODEL #	
MUDEL #	_
NAME #	
010 #	
SIS #	
AIA #	



#### **Crosswise Convection**

#### **Electric Convection Oven - 3 Grids**

697002 (ACF3E)

Electric convection oven, 3 grids, crosswise

## **Short Form Specification**

#### Item No.

Main structure in stainless steel, with seamless joints in the oven cavity. Cavity made from enamelled steel. Triple tempered glass door. Cavity lighting. 5 selectable cooking cycles: grilling, fast grilling, turbo grilling (for large pieces of meat), true fan cooking (for baking and roasting) and defrost. Max.temperature of 250°C. Functional level: basic, manual.

"Cross-wise" pan rack, 90 mm pitch, suitable for 3 grids mm 466x385. Supplied with: n. 3 grids (466x385), n. 1 enamelled tray (466x385x20h)

#### **Main Features**

- 5 selectable cooking functions:
  - Grilling (ideal to grill flat food items in small quantities or for toasts)
  - Fast grilling (to grill large quantities of flat food items or for toasts)

  - -Turbo grilling (for large pieces of meat) -True fan cooking (to roast or roast and bake with the same cooking temperature on more than one shelf) -Defrost (to thaw frozen food)
- Cavity lighting and "crosswise" pan supports allow clear and unobstructed view of the products being
- Superior cooking performances are guaranteed thanks to the complete air-o-flow coverage.
- Racks can be easily removed without the need for special tools.
- Maximum temperature of 250°C.
- Lighting function to activate the oven lamp without selecting a cooking function.
- Easy entry side grids to facilitate pan/grids insertion.
- Unit includes:

cooked.

- -3 grids (466x385)
- -1 enameled tray (466x385x20h)

#### Construction

- Oven exterior paneling in stainless steel.
- Enameled cooking chamber.
- Triple tempered glass door.
- · Height adjustable feet.

## **Optional Accessories**

•	Grid for	electric	convection	oven	with	3PNC	9210	03
	grids							

•	Enamelled tray (466x385x20) for	PNC 921004
	electric convection oven with 3 grids	



## Crosswise Convection Electric Convection Oven - 3 Grids

# **Front** 0 592. 635 42.5 450 74 Top 598 101 ΈI EI = Electrical connection Side 430 109

## **Electric**

Supply voltage:

**697002 (ACF3E)** 230 V/1N ph/50/60 Hz

Electrical power: 2.8 kW

### **Key Information:**

External dimensions, Height: 635 mm
External dimensions, Width: 600 mm
External dimensions, Depth: 615 mm
Net weight: 41 kg
Number of grids: 3

Type of grids: 385x466 mm
Runners pitch: 90 mm
Cooking cycles - air-convection: 250 °C
Internal dimensions, width: 480 mm
Internal dimensions, depth: 416 mm
Internal dimensions, height: 357 mm
Heating-up time (hot air cycle): 215°C / 724s.

Crosswise Convection Electric Convection Oven - 3 Grids